

**RETE ELETTROSALDATA STANDARD ITALIA PER CEMENTO ARMATO
IN ACCIAIO AL CARBONIO**



| Tipo | Diametro filo | Maglia | Dimensione pannello | Sezione resist. | Peso al m ² | Superficie pannello | Peso pannello |
|------|---------------|--------|---------------------|--------------------|------------------------|---------------------|---------------|
| | mm | cm | cm | cm ² /m | Kg | m ² | Kg |
| 510 | 5 | 10x10 | 200X300 | 1,97 | 3,130 | 6 | 18,870 |
| 510 | 5 | 10x10 | 225X400 | 1,97 | 3,130 | 9 | 28,170 |
| 515 | 5 | 15x15 | 200X300 | 1,31 | 2,090 | 6 | 12,540 |
| 515 | 5 | 15x15 | 225X400 | 1,31 | 2,090 | 9 | 18,810 |
| 520 | 5 | 20x20 | 200X300 | 0,98 | 1,591 | 6 | 9,546 |
| 520 | 5 | 20x20 | 225X400 | 0,98 | 1,591 | 9 | 14,310 |
| 610 | 6 | 10x10 | 200X300 | 2,82 | 4,489 | 6 | 26,934 |
| 610 | 6 | 10x10 | 225X400 | 2,82 | 4,489 | 9 | 40,320 |
| 615 | 6 | 15x15 | 200X300 | 1,88 | 3,014 | 6 | 18,084 |
| 615 | 6 | 15x15 | 225X400 | 1,88 | 3,014 | 9 | 27,000 |
| 620 | 6 | 20x20 | 200X300 | 1,41 | 2,293 | 6 | 13,578 |
| 620 | 6 | 20x20 | 225X400 | 1,41 | 2,293 | 9 | 19,800 |
| 810 | 8 | 10x10 | 200X300 | 5,03 | 8,010 | 6 | 48,060 |
| 810 | 8 | 10x10 | 225X400 | 5,03 | 8,010 | 9 | 72,000 |
| 815 | 8 | 15x15 | 200X300 | 3,35 | 5,372 | 6 | 32,232 |
| 815 | 8 | 15x15 | 225X400 | 3,35 | 5,372 | 9 | 48,330 |
| 820 | 8 | 20x20 | 200X300 | 2,51 | 4,082 | 6 | 24,492 |
| 820 | 8 | 20x20 | 225X400 | 2,51 | 4,082 | 9 | 36,720 |
| 1015 | 10 | 10x10 | 200X300 | 5,24 | 8,507 | 6 | 51,042 |
| 1015 | 10 | 10x10 | 225X400 | 5,24 | 8,507 | 9 | 76,500 |
| 1020 | 10 | 10x10 | 200X300 | 3,93 | 6,376 | 6 | 38,256 |
| 1020 | 10 | 10x10 | 225X400 | 3,93 | 6,376 | 9 | 57,330 |
| 1220 | 12 | 20x20 | 200X300 | 5,66 | 9,176 | 6 | 55,060 |
| 1220 | 12 | 20x20 | 225X400 | 5,66 | 9,176 | 9 | 82,530 |

SudFerro